

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3184B

SIMOTICS SD - 180 L - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{(3)}$			$\cos \phi^{(3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	22.00	-/-	41.00	1470	143.0	93.0	93.6	93.6	0.83	0.78	0.68	6.8	2.3	3.3	IE3
690	Y	50	22.00	-/-	24.00	1470	143.0	93.0	93.6	93.6	0.83	0.78	0.68	6.8	2.3	3.3	IE3
460	Δ	60	25.30	-/-	41.00	1770	136.0	93.6	94.1	94.0	0.83	0.78	0.69	6.9	2.2	3.2	IE3
460	Δ	60	22.00	-/-	36.50	1775	118.0	93.6	93.8	93.3	0.81	0.75	0.65	7.7	2.8	3.7	IE3
IM B35 / IM 2001		FS 180 L				IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 ° C - +40 ° C / 1000 m									Locked rotor time (hot / cold) : 26.4 s 41.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	68 / 75 dB(A) ^{2) 3)}	70 / 77 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.1400 kg m ²		Thermal class	F
Bearing DE NDE	6210 2Z C3	6210 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad min}$ for coupling operation 50 60Hz	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	170 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(A) without (Standard)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Cable diameter from ... to ...	19 mm - 28 mm
Material of terminal box	cast iron	Cable entry	2xM40x1,5
Type of terminal box	TB1 J01	Cable gland	2 plugs
Contact screw thread	M5		
Max. cross-sectional area	16 mm ²		

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1503-1EB43-4JA4			document number			
© Siemens AG 2023				rev. 3	creation date 2023-04-28	language en	Page 1/1