PRODUCT INFORMATION PACKET



Model No: D2851 Catalog No: D2851

1-3/4 HP OEM Replacement Motor, 1125/950 RPM, 1 Speed, 208-230/460 Volts, 48 Frame, Semi Enclosed

HVAC/R OEM Replacement Motors



Regal and Fasco are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2021 Regal Beloit Corporation, All Rights Reserved. MC017097E






Nameplate Specifications

Output HP	1-3/4 Hp	Output KW	0.75 kW	
Frequency	60 Hz	Voltage	208-230/460 V	
Current	3.95/2.10 A	Speed	1125/950 rpm	
Service Factor	1	Phase	1	
Duty	Continuous Air Over	Insulation Class	В	
Frame	48	Enclosure	Open Air Over	
Thermal Protection	Thermally Protected	Ambient Temperature	65 °C	
UL	Recognized	CSA	Υ	
CE	N			

Technical Specifications

Electrical Type	Permanent Split Capacitor	Poles	6
Rotation	Counterclockwise	Mounting	Lug
Motor Orientation	Hor	Drive End Bearing	Ball
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel
Shaft Type	Keyed	Overall Length	10.46 in
Frame Length	6. 07 in	Shaft Diameter	0.620 in
Shaft Extension	3. 25 in	Thru-bolts Extension	N/R in
Connection Drawing	NP24X350275	Outline Drawing	5KCP39UFWD73S


This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:05/03/2021



Incontrolled Copy

COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED.
PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF
REGAL BELOIT AMERICA, INC. ("OWNER") AND CONTAINS OWNER'S PROPRIETARY
INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED,
BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED
TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT
AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL
BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN
RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.

_	, <u> </u>					
	DRAWING REVISION	REVISION BY	DATE			
	Α	SB	1/12/2014			
ECO		APPROVED BY	DATE			
	ECO-0045207	SKK	1/12/2014			
	ECO DESCRIPTION					
	NEW CONNECTION DRAWING					



NOTES:

- TYPE FACE: COLORS OR NUMBERS DENOTING LEAD IDENTIFICATION AND N.P. NUMBER ARE TO BE 18 POINT NEWS GOTHIC CONDENSED. OTHER INFORMATION SHOULD BE 18 POINT IF SPACE ALLOWS, OTHERWISE USE 14 POINT.
- MATERIALS: 4 MIL WHITE VINYL ADHESIVE STOCK RBC SPEC A50FG41-S1 BLACK INK RBC SPEC A50FM48
- 3. THE BOX LINES AND DIMENSIONS REPRESENT THE SIZE OF THE TAPE TO BE USED. DO NOT INCLUDE THESE IN STAMP FORMAT.

