

Input data

System of measurement		Metric
Input type		Gear motor
Input speed	[rpm]	1400
Output speed	[rpm]	93.33
Ratio (i=)		15
Frequency	[Hz]	50
Input options		IEC
Requested input power	[kW]	0.37
Service factor		1.5
Rated Power P1	[kW]	0.55

Output data

Gear unit M RS 40 PC 15 71 B14 AC 19 MT 0.37 kW 71 B4 B14 X1 EL B3

Type		RS - Worm speed reducers
Input type		M
Size		40
Ratio (i=)		15
Input flange		B14
Mounting position		B3
Input speed	[rpm]	1400
Output speed	[rpm]	93.33
Rated output torque	[Nm]	29.53
Service Factor		1.5
Efficiency		0.78
Inertia moment	[kgm ²]	0.000019

Gear unit configuration

Output shaft	Hollow output shaft
Fixing	Shaft mounting
Version	PC

Output radial and axial loads

Ball bearings output radial load	[N]	1200
Taper bearings output radial load	[N]	1650
Ball bearings output axial load	[N]	240
Taper bearings output axial load	[N]	330

Accessories


Hollow output shaft	AC 19
---------------------	-------

Electric motor

Size		71 B4
Poles		4
Power	[kW]	0.37


Electric motor configuration

Motor flange	B14
Terminal box position	X1
Economic line motor	EL




Mounting positions


B3




B6




B7




B8




V5



V6



Terminal box position







0.08



← Oil quantity [litres]

Lubricant type: Long life synthetic oil ISO VG320

Direction of rotation



Weight

Gear unit [kg]	2.5
Electric motor [kg]	5.8

Gearing data

Axial module	2
Number of starts	2
Lead angle	11° 18'
Pressure angle	20°

Backdriving

Variable static self-locking
Quick back-driving in case of vibrations
Dynamic back-driving